

## VANDALISM Cameras

[Model Overview](#)
[Camera Overview](#)
[Features Overview](#)
[Price List](#)


### Indoor

| Features                 |                           | Variations     |      |
|--------------------------|---------------------------|----------------|------|
| <b>Resolution</b>        | 1280 x 960                | <b>Outdoor</b> |      |
| <b>Memory</b>            | 128 MB                    | <b>Indoor</b>  | IP54 |
| <b>Video Ring Buffer</b> | 64 MB                     | <b>Mono</b>    | x    |
| <b>Sensitivity</b>       | 1 lux                     | <b>Dual</b>    | x    |
| <b>Housing</b>           | Stainless steel<br>(3 mm) | <b>Day</b>     | x    |
| <b>Color</b>             | gray                      | <b>Night</b>   | x    |

### Camera Models

#### V12M-Sec



**Indoor** Mono, Vandalism-protected indoor camera for corner mounting with one color CMOS, 22mm Super wide-angle lens and power supply

2.498 €

Article numbers:  
MX-V12M-Sec-D22

#### V12D-Sec



**Indoor Dual**, Vandalism-protected indoor camera for corner mounting with one color and one b/w CMOS, 22mm Super wide-angle Day/ LowLight lenses and power supply

2.598 €

Article numbers:  
MX-V12D-Sec-D22N22

---

## Features

---

|                          |  |
|--------------------------|--|
| <b>Resolution</b>        | <b>2 x MEGA</b> , CMOS 1280 x 960 color (right) and black/white (IR-sensitive), sensitivity (color): 1 lux (t = 1/60 sec) / 0.05 lux (t = 1/1 sec), sensitivity (b/w): 0.1 lux (t=1/60 sec) / 0.005 lux (t = 1/1 sec), image formats: 1280x960, 640x480, 320x240, 160x120 pixels, customer defined   |
|                          | <b>Zoom:</b> Digital zoom 1x, 2x, 4x, software panning/tilting   |
| <b>Lenses</b>            | <b>L22 Super-wide-angle</b> 22 mm (90°Hx67°V; in 10m: 20.0m x 13.3m)<br><b>L43 Wide-angle</b> 43 mm (45°Hx34°V, in 10m: 8.2m x 6.1m)   |
| <b>Max. frame rate</b>   | <b>30 fps VGA, 30 fps CIF, 10 fps MEGA</b>   |
| <b>Interfaces</b>        | 10/100 Ethernet (RJ45), ISDN S0 (RJ45)*, RS232 (D-Sub 15 HD socket)*, 1 x In, 1 x Out (galv. isolated from power supp.)*   |
| <b>Sensors</b>           | Video Motion detector, Exposure zones, speaker and microphone, 24V switch input and output*  |
| <b>Features</b>          | Web Server, FTP client, e-Mail, ISDN PPP server/client, Multi View, recorder/player, softbuttons, RS232 data logger, RS232 Web terminal, IP Notify (Send, Receive) for ext. management systems, ISDN telephony, SIP video telephony and alarm messagings, IP announcement, PDA web pages, MxPEG Live, logo generator, snapshot recording (50 pre-, 50 post-alarm images), video audio recording (30 fps VGA), video audio recording (events), video audio recording (scheduled), scheduled privacy zones, flexible event logic, Master/Slave arming, 20 integrated IR LEDs |
| <b>Image Storage</b>     | <b>64 MB</b> internal image/event storage (approx. 4,000 images 320x240, high quality); event- and time-controlled storage: internal, via FTP on webserver or <b>PC on the LAN</b> (Windows/Linux NFS), images are directly accessible, no FTP required (although possible)  |
| <b>Dimensions</b>        | 248 x 185 x 153 mm (6.7" x 5.6" x 6.1")  |
| <b>Standard Delivery</b> | <b>Vandalism-protected stainless steel housing</b> (3 mm), gray, manual, Allen wrench, stainless steel screws with dowels, patch cable S/FTP yellow, 8-wire, 3 m (10'), EM-shielded; incl. power supply  |

## Warranty

12 months

\* Upon request

Valid as of: 04/11/2007 • Technical information subject to change without notice! • Suggested retail prices • Prices may vary by up to 15 percent depending on country • VAT to be added where applicable