

**Megapixel**  
1280 x 960  
software zoom

**30 Frames/s**  
VGA (640 x 480)  
10 F/s Mega

-22°F ... +140°F  
**Weatherproof**  
- 30° ... +60°C, IP65  
no heating necessary

IEEE 802.3af  
**PoE**  
network power  
even in winter

microphone & speaker  
**Audio**  
bi-directional via IP  
variable framerates

SIP-Client with video  
**IP-Telephony**  
alarm notify,  
cam remote control

**Video motion**  
multiple windows  
precision pixel-based

lip-synchronized audio  
**Recording**  
event-ringbuffer  
30 cams each 30 F/s

**Live viewing**  
30 cams at 30 F/s  
all on one screen

**Backlight**  
safe using CMOS  
without mechanical iris

**Wall bracket**  
with cable cover  
for RJ45 wall outlet

**Robust**  
no moving parts  
fiber glass housing

\* Sold only to distributors or commercial clients • Prices excl. VAT/sales tax • Set price without camera • Subject to change without notice

# D22: MOBOTIX IP-Dome

## High Resolution And Inexpensive

**NEW**

### D22 Basic



Ø 129 mm

Basic 448,-\*

*Camera prices include  
MxControlCenter software*

- Indoor dome camera (IP54) with lenses available from Super Wide-Angle (90°) to tele (15°)
- Includes L22 Super Wide-Angle lens (90°)
- For indoor use
- Surveillance of a complete room with only one camera
- PoE power supply according to IEEE 802.3af
- Image resolution VGA 640x480, 16 fps VGA

### D22 IT (VGA) and SECURE (MEGA)



Ø 160 mm



IT 548,-\*  
SEC 748,-\*

- Outdoor dome camera (IP65) with lenses available from Super Wide-Angle (90°) to tele (15°)
- Includes L22 Super Wide-Angle lens (90°)
- Connectors for external speaker and microphone, for VoIP and SIP telephony
- PoE power supply according to IEEE 802.3af
- IT: max. resolution 640x480, 30 fps VGA
- SEC: max. resolution 1280x960, 10 fps MEGA

### D22 IT/SEC + Vandalism Set



Ø 160 mm



Set 98,-\*

- Vandalism Set for IT and Secure models
- Consists of stainless steel cover (matt, polished, white, silver or black powder-coated), security screws
- Reinforced dome (3 mm polycarbonate)
- Ideally suited for surveillance at extremely critical locations
- Temp. range -30 to +60°C (-22 to +140°F), IP65

### D22 IT/SEC + On Wall Set



Ø 165 x 37 mm



Set 98,-\*

- On-Wall Set for IT and Secure camera models
- Consists of On-Wall Mount and mounting parts
- Also conforms to U.S. installation standards
- Reliably protects the cabling and allows integrating additional modules within the On-Wall Mount
- Temp. range -30 to +60°C (-22 to +140°F), IP65

### D22 IT/SEC + Outdoor Wall Mount



Set 98,-\*

- Outdoor Wall Mount for IT and Secure camera models
- Consists of Outdoor Wall Mount and mounting parts
- Covers RJ45 wall outlets
- Space for expansion modules (battery, 3G, WiFi, etc.)
- Easily mounted to poles using Pole Mount

### D22 IT/SEC + In Ceiling Set



Set 98,-\*

- In-Ceiling Set for IT and Secure camera models
- Concealed installation in ceilings
- Suitable for hidden surveillance