

# MOBOTIX HiRes IP Cameras D22



... the new face of IP video

**NEW**  
D22 FixDome



Model:	D22Mi-Basic-D22	D22M-IT-D22	D22M-IT-Night-N22	D22M-Sec	D22M-Sec-Night
<b>Indoor/Outdoor:</b>	Indoor, IP54, -30..+50°C	In/Outdoor, IP65 weatherpr., -30..+60°C	In/Outdoor, IP65 weatherpr., -30..+60°C	In/Outdoor, IP65 weatherpr., -30..+60°C	In/Outdoor, IP65 weatherpr., -30..+60°C
<b>Resolution:</b>	VGA (640x480 pixels), color	VGA (640x480 pixels), color	VGA (640x480 pixels), <b>BW</b>	<b>MEGA</b> (1280x960 pixels), color	<b>MEGA</b> (1280x960 pixels), <b>BW</b>
<b>Pan/Tilt/Zoom:</b>	./.	./.	./.	1x, 2x, 4x • Zoom & Pan/Tilt (digital)	1x, 2x, 4x • Zoom & Pan/Tilt (digital)
<b>Frame Rate (Mono):</b>	16 fps VGA • 16 fps CIF	<b>30 fps VGA</b> • 30 fps CIF	<b>30 fps VGA</b> • 30 fps CIF	<b>30 fps VGA</b> • 30 fps CIF • 10 fps Mega	<b>30 fps VGA</b> • 30 fps CIF • 10 fps Mega
<b>Sensitivity:</b>	1 lux (t=1/60sec) • 0.05 lux (t=1/1sec)	1 lux (t=1/60sec) • 0.05 lux (t=1/1sec)	0.1 lux (t=1/60sec) • 0.005 lux (t=1/1sec)	1 lux (t=1/60sec) • 0.05 lux (t=1/1sec)	0.1 lux (t=1/60sec) • 0.005 lux (t=1/1sec)
<b>Interfaces:</b>	Ethernet 10/100 Mbps	Ethernet 10/100 Mbps, USB, ext. audio	Ethernet 10/100 Mbps, USB, ext. audio	Ethernet 10/100 Mbps, USB, ext. audio	Ethernet 10/100 Mbps, USB, ext. audio
<b>Video Ring Buffer:</b>	2 MB	32 MB/up to 1 Terabyte externally	32 MB/up to 1 Terabyte externally	64 MB/up to 1 Terabyte externally	64 MB/up to 1 Terabyte externally
<b>Audio/Telephony:</b>	./.	Bidirectional, VoIP, IP Telephony	Bidirectional, VoIP, IP Telephony	Bidirectional, VoIP, IP Telephony	Bidirectional, VoIP, IP Telephony
<b>Power Sup. • In/Out:</b>	PoE or MX30V • N/A	PoE or MX30V • Via Mini USB	PoE or MX30V • Via Mini USB	PoE or MX30V • Via Mini USB	PoE or MX30V • Via Mini USB
<b>Software Features:</b>	FTP, e-mail, video alarm management, video motion, MultiView, event search	FTP, e-mail, video alarm management, video motion, MultiView, event search	FTP, e-mail, video alarm management, video motion, MultiView, event search	FTP, e-mail, video alarm management, video motion, MultiView, event search	FTP, e-mail, video alarm management, video motion, MultiView, event search
<b>Arming • Triggering:</b>	./.	Annual time table • Event logic	Annual time table • Event logic	Annual time table • Event logic	Annual time table • Event logic
<b>External Storage:</b>	./.	Ring buffer on PC/server/NAS	Ring buffer on PC/server/NAS	Ring buffer on PC/server/NAS	Ring buffer on PC/server/NAS
<b>Lenses: (eq. 35mm)</b>	Super Wide-Angle (22mm, 90°, F 2.0)	Super Wide-Angle (22mm, 90°, F 2.0)	Super Wide-Angle (22mm, 90°, F 2.0)	Super Wide-Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm	Super Wide-Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
<b>Prices:</b>	448 EUR	548 EUR	548 EUR	748 EUR	748 EUR

MOBOTIX Cost Benefits
• Increased resolution reduces amount of cameras needed
• Reduced installation costs
• Intelligent recording technology reduces required storage
• Event-controlled image rate minimizes storage costs
• No additional power (standard PoE) and no heating required
• Backup power requirement reduced by 8 times
• Robust and practically maintenance free
• No software and no license costs
• Unlimited scalability and high return of investment
• Additional functions and other extras included

Lenses 1/2", M14 lens distortion can be removed using MxControlCenter



\* M22M special order

## MOBOTIX accessories for D22 IT/SECURE models (see other products in the price list)

<b>Part Name:</b>	<b>D22 Vandalism Set</b>	<b>D22 On-Wall Set</b>	<b>D22 In-Ceiling Set</b>	<b>D22 Corner and Pole Mount</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>Reinforced dome (3mm Polyc.)</li> <li>Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)</li> </ul>	<ul style="list-style-type: none"> <li>On-wall mount incl. mounting parts</li> <li>Concealed cabling</li> <li>Ø 165x37mm/6.5x1.5in</li> </ul>	<ul style="list-style-type: none"> <li>In-ceiling set incl. mounting parts</li> <li>Concealed camera positioning</li> <li>Ø 150mm/5.9in diameter</li> </ul>	<ul style="list-style-type: none"> <li>3mm stainless steel, powder-coated</li> <li>Pole diam.: 60 to 180mm/2.4 to 7.1in</li> <li>Incl. mounting supplies</li> </ul>
<b>Prices:</b>	98 EUR	98 EUR	98 EUR	98 EUR

